



Warranty

We warrant that the Tyre Trek product will be free from defects in materials and workmanship for a period of one year from the date of purchase. Please retain your Proof of purchase. If the product proves defective during the warranty period, we will at our option either:

1. repair the product;
2. replace the product;
3. refund the amount paid for the product, less a reasonable allowance for usage, upon its return.

These warranties shall not apply to any defect, failure or damage caused by improper use or improper or inadequate installation, maintenance or care. The obligations of the warranty shall not be applicable if the installation and maintenance procedures set out below are not adhered to. No warranty is given if there is evidence of overloading, welding, drilling or if any other form of misuse is found.

The following listed items have a limited warranty of 120 days from purchase date:

LED number plate light, bearings and seal, any damaged caused by failure of bearings, the over centre latch and powdercoating. These items can be subject to wear and failure over a period of time.

THE ABOVE WARRANTIES ARE GIVEN WITH RESPECT TO THE PRODUCT IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED. WE DISCLAIM ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY SIMILAR STANDARD IMPOSED BY APPLICABLE LEGISLATION. OUR RESPONSIBILITY TO REPAIR, REPLACE OR OFFER A REFUND FOR DEFECTIVE PRODUCTS AND RELATED ITEMS IS THE SOLE AND EXCLUSIVE REMEDY PROVIDED TO THE CUSTOMER FOR BREACH OF THESE WARRANTIES.

This warranty does not affect your rights under Australian consumer law.

TO THE EXTENT ALLOWED BY LAW, EXCEPT FOR THE OBLIGATIONS SPECIFICALLY SET FORTH IN THIS WARRANTY STATEMENT, IN NO EVENT SHALL WE BE LIABLE FOR ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOSS OF PROFITS) WHETHER BASED ON CONTRACT, TORT OR ANY OTHER LEGAL THEORY AND IRRESPECTIVE OF WHETHER WE HAVE ADVANCE NOTICE OF THE POSSIBILITY OF SUCH DAMAGE.

Installation - Notice: Only fit this unit to a towbar with a 2000 kg or greater towing capacity.

Step 1 Remove your trailer ball mount from your tow bar.

Step 2 Insert the Tyre Trek into your tow bar and pin the unit in the required hole so that you have a minimum distance of 25mm between the back of your vehicle and the back of the Tyre Trek or if fitted with a Jerry can holder maintain a 25mm distance.

Step 3 Lock the Tyre Trek into place by tensioning up the locking bolt at the bottom of the unit. To ensure the unit is locked in correctly follow these steps:

1. Apply minimal tension to the locking bolt then stop and give the unit a lift up and down on the end of the swing arm. This lets the unit seat itself in the towbar.
2. Finish tightening up the locking bolt to a maximum of 80Nm of pressure. DO NOT OVER TIGHTEN OR DAMAGE MAY OCCUR.
3. Have the number plate light wired. If your number plate is obstructed on the back of your vehicle relocate it to the number plate bracket on the Tyre Trek.

Only fit Tyre Trek Jerry holder or shovel holder to this unit.

Owner is required to have number plate light connected.

Maintenance

Over a period of time dust can get into the main locking insert of the Tyre Trek and obstruct and hinder the locking unit. To prevent this you should remove the Tyre Trek from your towbar then undo the locking bolt completely and remove locking device. Clean all parts, apply antiseize to the thread of locking bolt and reassemble. This procedure should be done every 3 – 4 months, depending on the nature of terrain and conditions.